














**COLORI / COLORS**



Elemento di presa della griglia

**SCHEDA ORDINE PRODOTTO / PRODUCT ORDER DATA SHEET**

COD.	MOD.*					
GSP20-01	20x20		1	1332	120x120x120	0,350 kg/pz
GSP30-01	30x30		1	480	120x120x120	0,858 kg/pz
GSP40-01	40x40		1	234	120x120x120	1,960 kg/pz
GSP55-01	55x55		1	100	120x120x120	6,700 kg/pz
GSP20-02	20x20		1	1332	120x120x120	0,286 kg/pz
GSP30-02	30x30		1	480	120x120x120	0,660 kg/pz
GSP40-02	40x40		1	234	120x120x120	1,640 kg/pz
GSP55-01V	55x55		1	100	120x120x120	5,360 kg/pz

\*MEASURES IN CENTIMETERS

**GRIGLIA SINGOLA "TOP"**

Prodotta da GRUPPO STAMPLAST ha un design semplice ed una buona resistenza agli agenti atmosferici. Rispetto alla versione "NOR" la griglia è stata rinforzata per ottenere una migliore resistenza meccanica.

**Materiale:**

- Polipropilene Copolimero caricato con anti UV.
- Colorante per la versione verde.

**SINGLE GRATING "TOP"**

Manufactured by GRUPPO STAMPLAST it has a simple design and a good resistance to the atmospheric agents. Compared to the version "NOR" the grating has been reinforced providing better mechanical resistance.

**Material:**

- Stabilized Polypropylene Copolymer with anti UV.
- Dye for green version.

**SCHEDA TECNICA PRODOTTO / TECHNICAL SHEET**

MOD.*	A*	H*	Carico di rottura / Breaking load
20x20	18,5	2,9	6,1kN
30x30	28	3,8	11,4kN
40x40	38	3,8	21,4kN
55x55	53	4,9	41,7kN

\*MEASURES IN CENTIMETERS

